H61M-C

Intel® Socket 1155 for 3rd/2nd Generation Pentium®/Celeron® Processors
Supports Intel® 22 nm CPU
Supports Intel® 32 nm CPU
Supports Intel® Turbo Boost Technology 2.0
* The Intel® Turbo Boost Technology 2.0 support depends on the CPU types.
* Refer to www.asus.com for CPU support list

Chipset

Intel® H61

Memory

2 x DIMM, Max. 16GB, DDR3 2200(O.C.)/2133(O.C.)/2000(O.C.)/1866(O.C.)/1600/1333/1066 MHz Non-ECC, Un-buffered Memory
Dual Channel Memory Architecture
* Refer to www.asus.com for the Memory QVL (Qualified Vendors Lists).
* Due to OS limitation, when installing total memory of 4GB capacity or more, Windows® 32-bit operation system may only recognize less than 3GB. Install a 64-bit Windows® OS when you want to install 4GB or more memory on the motherboard.

Graphic

Integrated Graphics Processor
- Supports RGB with max. resolution 2048 x 1536 @ 75 Hz
Maximum shared memory of 1696 MB

Expansion Slots

1 x PCIe 3.0/2.0 x16
1 x PCIe 2.0 x1
1 x PCI

Storage

Intel® H61(B3) chipset :
4 x SATA 3Gb/s port(s), black

LAN

Realtek® 8111F, 1 x Gigabit LAN Controller(s)

- Audio

Realtek® ALC887 8-Channel High Definition Audio CODEC *[1]

- USB Ports

Built-in Controller :
10 x USB 2.0 port(s) (4 at back panel, , 6 at mid-board)

- Special Features

ASUS Exclusive Features :
- AI Suite II
- Ai Charger
- Anti-Surge
- ASUS UEFI BIOS EZ Mode featuring friendly graphics user interface
- Network iControl

ASUS Quiet Thermal Solution :
- ASUS Fan Xpert

ASUS EZ DIY :
- ASUS CrashFree BIOS 3
- ASUS EZ Flash 2
- ASUS MyLogo 2

100% All High-quality Conductive Polymer Capacitors

- Back I/O Ports

1 x PS/2 keyboard (purple)
1 x PS/2 mouse (green)
1 x D-Sub
1 x LAN (RJ45) port(s)
4 x USB 2.0
1 x COM port(s)
1 x Parallel port(s)
3 x Audio jack(s)

- Internal I/O Ports

3 x USB 2.0 connector(s) support(s) additional 6 USB 2.0 port(s)
4 x SATA 3Gb/s connector(s)

1 x CPU Fan connector(s) (1 x 4 -pin)
1 x Chassis Fan connector(s) (1 x 4 -pin)
1 x S/PDIF out header(s)
1 x 24-pin EATX Power connector(s)
1 x 4-pin ATX 12V Power connector(s)
1 x Front panel connector(s)
1 x Front panel audio connector(s) (AAFP)
1 x Internal speaker connector(s)
1 x Clear CMOS jumper(s)

- Accessories

User's manual
I/O Shield
2 x SATA 3Gb/s cable(s)

- BIOS

64Mb Flash ROM, UEFI BIOS, PnP, DMI v2.0, WfM2.0, SMBIOS v2.7, ACPI v2.0a,SLP3.0, EUP-ready

- Manageability

WOL, PXE, PME Wake Up

- Support Disc

Drivers
ASUS Utilities
ASUS Update
Anti-Virus Software (OEM Version)

- Form Factor

uATX Form Factor
9 inch x 7 inch (22.6 cm x 17.8 cm)

- Note

*1:Use a chassis with HD audio module in the front panel to support an 8-channel audio output.
Warranty: 3 Year Warranty